

## WALL CHARGER COLLECTION

## 15W stripe single

## TYPE-A



## SPECIFICATION

<b>Input</b>	Voltage	90~264Vac
	Frequency	47~63Hz
	Configuration	2Pin Socket (Live, Neutral)
<b>Output</b>	Voltage / Current	5V / 2A, 9V / 1.67A
	Ripple & Noise	150mVp-p Max.
	Wattage	15W Max.
	Configuration	USB Type-A
	Efficiency	Ave. 84.63% Min. (LEVEL 6)
<b>Protection</b>	OCP(Over Current Protection)	Auto Recovery
	SCP(Short Circuit Protection)	Auto Recovery
	OVP(Over Voltage Protection)	Auto Recovery
<b>Reliability</b>	Surge Immunity	Ring wave 6kV / Combination wave 2.5kV
	ESD Immunity	Contact: ±8kV / Air: ±15kV
	Case Temperature	131°F Max.
	Acoustic Noise	25dB Max.
<b>Safety</b>		IEC / EN 62368-1, 60950-1 (Worldwide)
<b>Form &amp; Size</b>		Wall mount 1.46 X 0.93 X 2.89 inch 37.0 X 23.5 X 73.3 mm

## 15W slim single

## TYPE-C



## SPECIFICATION

<b>Input</b>	Voltage	90~264Vac
	Frequency	47~63Hz
	Configuration	2Pin Socket (Live, Neutral)
<b>Output</b>	Voltage / Current	5V / 2A, 9V / 1.67A
	Ripple & Noise	150mVp-p Max.
	Wattage	15W Max.
	Configuration	USB Type-C
	Efficiency	Ave. 84.63% Min. (LEVEL 6)
<b>Protection</b>	OCP(Over Current Protection)	Auto Recovery
	SCP(Short Circuit Protection)	Auto Recovery
	OVP(Over Voltage Protection)	Auto Recovery
<b>Reliability</b>	Surge Immunity	Ring wave 4kV / Combination wave 1.5kV
	ESD Immunity	Contact: ±8kV / Air: ±15kV
	Case Temperature	55°C Max. (Tc-Tamb)
	Acoustic Noise	25dB Max.
<b>Safety</b>		IEC/EN 62368-1, 60950-1 (Worldwide)
<b>Form &amp; Size</b>		Wall mount 35.8 X 14.2 X 74.1 mm

## WALL CHARGER COLLECTION

# 25W slim single

## TYPE-C



## SPECIFICATION

<b>Input</b>	Voltage	90~264Vac
	Frequency	47~63Hz
	Configuration	2Pin Socket (Live, Neutral)
<b>Output</b>	Voltage / Current	PDO : 5V/3A, 9V/2.77A Support PPS
	Ripple & Noise	300mVp-p Max.
	Wattage	25W Max.
	Configuration	USB Type-C
<b>Efficiency</b>	Efficiency	Ave. 86.85% Min. (LEVEL 6)
	Standby Power	0.02W Max.
<b>Protection</b>	OCP(Over Current Protection)	Auto Recovery
	SCP(Short Circuit Protection)	Auto Recovery
	OVP(Over Voltage Protection)	Auto Recovery
<b>Reliability</b>	Surge Immunity	Ring wave 6kV / Combination wave 2.5kV
	ESD Immunity	Contact: ±8kV / Air: ±15kV
	Case Temperature	60°C Max. (Tc-Tamb)
	Acoustic Noise	25dB Max.
<b>Safety</b>		IEC/EN 62368-1, 60950-1(World Wide)
<b>Form &amp; Size</b>		Wall mount 35.8 X 23.66 X 78.2 mm

# 25W stripe single

## TYPE-C



## SPECIFICATION

<b>Input</b>	Voltage	90~264Vac
	Frequency	47~63Hz
	Configuration	2Pin Socket (Live, Neutral)
<b>Output</b>	Voltage / Current	PDO : 5V/3A, 9V/2.77A Support PPS
	Ripple & Noise	300mVp-p Max.
	Wattage	25W Max.
	Configuration	USB Type-C
<b>Efficiency</b>	Efficiency	Ave. 86.85% Min. (LEVEL 6)
	Standby Power	0.02W Max.
<b>Protection</b>	OCP(Over Current Protection)	Auto Recovery
	SCP(Short Circuit Protection)	Auto Recovery
	OVP(Over Voltage Protection)	Auto Recovery
<b>Reliability</b>	Surge Immunity	Ring wave 6kV / Combination wave 2.5kV
	ESD Immunity	Contact: ±8kV / Air: ±15kV
	Case Temperature	60°C Max. (Tc-Tamb)
	Acoustic Noise	25dB Max.
<b>Safety</b>		IEC/EN 62368-1, 60950-1(World Wide)
<b>Form &amp; Size</b>		Wall mount 41.3 X 26.1 X 78.1 mm

WALL CHARGER COLLECTION

# 45W stripe 2port

## TYPE-A, C



SPECIFICATION

<b>Input</b>	Voltage	90~264Vac
	Frequency	47~63Hz
	Configuration	2Pin Socket (Live, Neutral)
<b>Output</b>	Voltage / Current	C-Port PDO : 5V/3A, 9V/3A, 15V/3A, 20V/3.25A Support PPS A-Port 15W (QC, AFC) : 5V/2A,9V/1.67A
	Ripple & Noise	300mVp-p Max.
	Wattage	45W Max.
	Configuration	USB Type-C, Type-A
	Efficiency	Ave. 85.15% Min. 2Port (LEVEL 6)
<b>Protection</b>	Standby Power	0.1W Max.
	OCP(Over Current Protection)	Auto Recovery
	SCP(Short Circuit Protection)	Auto Recovery
	OVP(Over Voltage Protection)	Auto Recovery
<b>Reliability</b>	Surge Immunity	Ring wave 6kV / Combination wave 1.5kV
	ESD Immunity	Contact: ±8kV / Air: ±15kV
	Case Temperature	40°C Max. (Tc-Tamb)
	Acoustic Noise	25dB Max.
<b>Safety</b>		IEC/EN 62368-1, 60950-1(World Wide)
<b>Form &amp; Size</b>		Wall mount 43.5 X 28.0 X 84.8 mm

# 65W stripe single

## TYPE-C



SPECIFICATION

<b>Input</b>	Voltage	90~264Vac
	Frequency	47~63Hz
	Configuration	2Pin Socket (Live, Neutral)
<b>Output</b>	Voltage / Current	PDO : 5V/3A, 9V/3A, 15V/3A, 20V/3.25A Support PPS
	Ripple & Noise	300mVp-p Max.
	Wattage	65W Max.
	Configuration	USB Type-C
	Efficiency	Ave. 88.5% Min. @20V (LEVEL 6)
<b>Protection</b>	DPMS (No Load)	0.03W Max.
	OCP(Over Current Protection)	Auto Recovery
	SCP(Short Circuit Protection)	Auto Recovery
	OVP(Over Voltage Protection)	Auto Recovery
<b>Reliability</b>	Surge Immunity	Ring wave 6kV / Combination wave 2.5kV
	ESD Immunity	Contact: ±8kV / Air: ±15kV
	Case Temperature	65°C Max. (Tc-Tamb)
	Acoustic Noise	25dB Max.
<b>Safety</b>		IEC/EN 62368-1 (Worldwide)
<b>Form &amp; Size</b>		Wall mount 48.0 X 28.0 X 87.3 mm

## WALL CHARGER COLLECTION

# 65W stripe 3port

## TYPE-A, 2C



## SPECIFICATION

<b>Input</b>	Voltage	90~264Vac
	Frequency	47~63Hz
	Configuration	2Pin Socket (Live, Neutral)
<b>Output</b>	Voltage / Current	C1-Port PDO : 5V/3A, 9V/3A, 15V/3A, 20V/3.25 <sup>a</sup> C2-Port PDO : 5V/3A, 9V/2.77A Support PPS A-Port 15W (QC, AFC): 5V/3A,9V/1.67A
	Ripple & Noise	300mVp-p Max.
	Wattage	65W Max.
	Configuration	USB Type-C*2, Type-A
<b>Efficiency</b>	Efficiency	Ave. 86.5% Min. (Trio)
	DPMS (No Load)	0.1W Max.
<b>Protection</b>	OCP(Over Current Protection)	Auto Recovery
	SCP(Short Circuit Protection)	Auto Recovery
	OVP(Over Voltage Protection)	Auto Recovery
<b>Reliability</b>	Surge Immunity	Ring wave 6kV / Combination wave 2.5kV
	ESD Immunity	Contact: ±8kV / Air: ±15kV
	Case Temperature	65°C Max. (Tc-Tamb)
	Acoustic Noise	25dB Max.
<b>Safety</b>		IEC/EN 62368-1, 60950-1(World Wide)
<b>Form &amp; Size</b>		Wall mount 52.0 X 30.0 X 108.3 mm